



TECHNICAL DATA SHEET

SUPERWEB-GLIDE RANGE.

Description

These products are aqueous emulsions of a speciality formulated wax, for use in printing where UV print can not tolerate silicones.

They find use as release aids, lubricants, anti-rub aids, and surface finish additives on heat set, web offset printing press machines. The products offer additional gloss over standard emulsions when used in the printing of magazines and matt papers. They can also be used as a lubricant, softener or raising aid in the textile industry. The products have also found to be effective bases for polish formulations.

All these SuperWebGlides grades can be diluted with water shortly before use, or used neat, making them extremely cost effective products where applications require a more dilute product. SuperWeb 40P contains additional anti-static agent for improved performance on equipment where static causes processing problems.

Typical Properties

Appearance	Creamy White liquid
Odour	Pleasant waxy odour
Specific Gravity	0.98 – 0.99
Emulsion type	Non-ionic / Cationic
Brookfield Viscosity	50-200 cps
pH	5 – 6

Product Range

SuperWebGlide 15	15/5, 15/10, 15/20
SuperWebGlide 40	40, 40SH, 40P, 40N

Pack Size

Available in 25kg kegs, 200kg drums or 1 tonne bulk containers.

Shelf Life

12 Months From date of manufacture, Protect from Frost at all times.